

Pairing to an Android device

1. Download the **First-Link™** app from Google Play. If the **First-Link** app is already installed on your device, check for and download the latest update.
2. Go to **Settings**, select **Connections**, and make sure **Bluetooth** is turned **On**.
3. Plug the **Blue-Link 2** into the vehicle's diagnostic connector
4. Hold the button on the front of the **Blue-Link 2** for 3-5 seconds. The green light below the button will start flashing blue, indicating that the **Blue-Link 2** is discoverable.
5. Expand **Bluetooth** options. Then under **Available Devices**, select your **Blue-Link 2** device. It will display as **BL_** followed by the **Serial Number** of your **Blue-Link 2**.

6. Follow instructions provided by the diagnostics application.
7. Once paired, reference the following **Blue-Link 2** LED status indicator codes:

Solid Green

Powered up

Blinking Blue

Bluetooth communications

Blinking Green

Wi-Fi communications

Solid Blue

Connected to Wireless Access Point



First-Link app from Google Play

QUICK START GUIDE



Blue-Link™ 2

How to pair the Blue-Link 2 to an iOS or Android device.

For technical assistance, please call Customer Support at 1-800-639-6774.

Pairing to an iOS device

1. Download the **First-Link™** app from the App Store. If the **First-Link** app is already installed on your device, check for and download the latest update.
2. Go to **Settings** on your device and make sure **Bluetooth** is turned **On**.
3. Plug the **Blue-Link 2** into the vehicle's diagnostic connector
4. Follow pairing instructions provided by the diagnostics application.

5. Once paired, reference the following **Blue-Link 2** LED status indicator codes:

Solid Green

Powered up

Blinking Blue

Bluetooth communications

Blinking Green

Wi-Fi communications

Solid Blue

Connected to Wireless Access Point



First-Link app from the App Store

Product Specifications

The Blue-Link 2 is configured with the following specifications:

Feature	Data
Physical Dimensions	3.5" x 2.25" x 1.625" (89mm X 57.15mm x 41.28mm)
Weight	2.4oz (0.068kg)
Power Requirements	6-32VDC @ 1200mA (MAX)
Operating Temperature	0 to 50 °C 32 to 122 °F

NEXIQ
TECHNOLOGIES®

NEXIQ Technologies is a registered trademark, and *Blue-Link* and *First-Link* are trademarks of IDSC Holdings LLC.
©2023 IDSC Holdings LLC. All rights reserved.
Part No. ZEESM608A1